

Q8 T750 15W-40

Description

Q8 T750 15W-40 is a Super High Performance Diesel Engine Lubricant designed for the lubrication of low emission Euro IV & Euro V engines.

Application

Q8 T750 15W-40 can be used in all high performance four stroke diesel engines operating on low sulphur diesel fuel (<0.05 % mass) and under severe heavy duty conditions. Extended oil drain intervals as indicated by the OEM for high quality diesel engine oils can be applied.

The diesel engines may be normally aspirated, turbo-charged or super-charged, with or without inter-cooling and fitted in commercial vehicles or off-highway equipment.

It is also suitable for application in passenger cars with petrol or diesel engines.

Specifications

- API CI-4/SL
- ACEA E7, E5, E3, B4, A3
- Global DHD-1
- MAN M3275
- MB 228.3
- Volvo VDS-3
- MTU Type 2
- Renault VI RLD & RLD-2
- Deutz DQC III-10
- Cummins CES 20071, -72, -76, -77
- Caterpillar ECF-1 & ECF-2
- Mack EO-N
- ZF TE-ML 04C, 07C
- Exceeds requirements of DAF, IVECO and Scania

Benefits

- Excellent protection against bore polishing and cam wear
- Offers prolonged oil drain intervals and reduces maintenance costs
- Protects engine against corrosive wear in off-the-road applications
- Provides quick lubrication after cold starting thus limiting engine wear
- Prevents engine fouling due to combustion soot
- Performance quality allows wide application from cars to trucks
- Universal engine oil suitable for passenger cars, trucks and off-road applications

Typical Inspection Data

Property	Method	Unit	Inspection Data
Absolute Density, 15 °C	D 1298	kg/m ³	886
Kinematic Viscosity, 40 °C	D 445	mm ² /s	104.6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.0
Viscosity Index	D 2270	-	135
Borderline Pumping Temperature	D 3829	°C	- 25
Flash Point,	D 93	°C	210
Pour Point	D 97	°C	- 27
Total Base Number	D 2896	mg KOH/g	10.0
Sulphated Ash Content	D 874	% mass	1.4

Health and Safety

Reference should be made to the relevant Q8 Material Safety Data Sheet before use.

Feb 12



Kuwait Petroleum International Lubricants (UK) Ltd

Knowsthorpe Gate, Leeds LS9 0NP. UK

For further assistance contact the Technical help line Telephone +44 (0) 113 2365 223, Fax +44 (0) 870 238 4673

For Customer Sales Contact, Tel +44 (0) 113 2365 204, Fax +44 (0) 113 2485 026. www.Q8Oils.co.uk

In line with our policy of continued improvement, Kuwait Petroleum International Lubricants reserve the right to change specification and availability without prior notice

technical data



Certificate No. FM 89665