



TITAN TRUCK PLUS 15W-40

High Performance oil for a variety of diesel and gasoline engines. Specially for highly loaded commercial vehicle diesel engines. Lower oil consumption.

Description

TITAN TRUCK PLUS 15W-40 is a super long term all season engine oil of the SHPD category for diesel and gasoline engines with and without turbo charging in passenger cars, trucks, buses and industrial equipment that have high requirements with respect to engine cleanliness and maintenance intervals. TITAN TRUCK PLUS 15W-40 complies with and/or fulfils and exceeds the requirements of American and European engine manufacturers thanks to its special formulation, especially engines with fill specifications CUMMINS CES 20071/-2/-6/-7/-8 and VOLVO VDS-3. Due to its advanced design, TITAN TRUCK PLUS 15W-40 ensures operation without problems under all climatic conditions.

Application

TITAN TRUCK PLUS 15W-40 has a significantly more modern additive system than the usual HD engine oils of the same SAE class. Independently of the odometer reading, all commercial vehicle diesel engines can be changed over to TITAN TRUCK PLUS 15W-40. Important for shipping companies that operate internationally, bus operations, construction companies, etc. is also that TITAN TRUCK PLUS 15W-40 can be used even with higher sulphur content diesel fuel, while with the usual HD engine oils this can often lead to considerable problems. TITAN TRUCK PLUS 15W-40 is most suitable for use in EURO 3 engines. TITAN TRUCK PLUS 15W-40 is miscible and compatible with conventional branded engine oils. However, intermixtures with other engine oils should be avoided in order to fully utilise the product's benefits. Respectively a complete oil change is recommended when converting to TITAN TRUCK PLUS 15W-40.

Advantages/Benefits

- Excellent wear protection even under high continuous stress
- Protection from corrosion even when used with diesel fuels with high sulphur content
- Sludge and deposits are prevented by TITAN TRUCK PLUS 15W-40 under extraordinarily high thermal loads as well as in stop and go driving

Specifications

- ACEA E7
- API CI-4/SL
- GLOBAL DHD-1
- CAT ECF-1-a/ECF-2

Approvals

- CUMMINS CES 20076/7/8
- DEUTZ DQC III
- MACK EO-N
- MAN M 3275-1
- MB-APPROVAL 228.3
- MTU DDC TYPE-2
- RENAULT RLD / RLD-2
- VOLVO VDS-3

FUCHS Recommendations

- ACEA A3/B4
- ALLISON C-4
- CAT TO-2
- CASE MS 1121
- CUMMINS CES 20071/2
- DAF
- IVECO 18-1804 CLASSE T2 E7
- NH 330 H
- STEYR A-201

December 2011 GDUK Page 1 of 2

Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products



CHARACTERISTICS: TITAN TRUCK PLUS 15W-40

Density at 15°C	DIN 51757	0.886 g/ml
Flash Point, CoC	DIN ISO 2592	233°C
Pour Point	DIN ISO 3016	-36°C
Kinematic Viscosity at 40°C	DIN 51562-1	107.9 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	14.6 mm ² /s
Viscosity Index	DIN ISO 2909	139

December 2011 GDUK Page 2 of 2

Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products